DA

Thinner and cleaner for antifouling





PRODUCT DESCRIPTION

Nautix **DA** thinner/cleaner is suitable for all Nautix antifoulings. This product is particularly recommended to make easier application of antifouling and to clean tools.

Nautix **DA** is also recommended to clean spots of tar and rust, and remove splashes.

Nautix **DA** can be used with following products:

- Nautix antifoulings
- Nautix Deck Grip

PRODUCT INFORMATION

Finish Translucent Flash point $FP > 47^{\circ}C$ Packaging 0.75L - 2.5L Shelf life 5 years

SAFETY INFORMATION

- Work in well-ventilated area (ensure adequate ventilation during use), wear suitable protective clothing, gloves, glasses and eye/face
 protection. Unprotected person must be kept away from treatment area. Dispose of protective gloves and equipment after use.
- Read the label safety section for Health and Safety Information before application.

APPLICATION

Roller/ Brush

Dilution 5 to 10% max.

Spray gun

Dilution 15 to 25%.

Airless pump.

• No dilution or 5% maximum.

Application advices

Be careful: Dilution increases dramatically drying time before recovering.

If substantial dilution : Apply only thin layers to allow quick evaporation of solvents.

It's recommended to dilute up to 25% maximum to avoid damaging the technical properties of paint : Film rupture or quick encrustation.

TRANSPORT, STORAGE, AND SAFETY INFORMATION

Transport and storage

- Product should be kept in securely closed and solvent-resistant containers during transport and storage.
- Exposure to air, sun, and extreme temperatures should be avoided. For the full shelf-life of the paint, be sure that the container is firmly
 closed between use and the storage temperature is between 10° and 25°C. Keep out of direct sunlight.

Safety

• Before use, read the label safety section for Health and Safety Information. For further details, please contact Nautix or its distributors.

Waste

Disposal of remainders must be arranged for in consultation with the authorities. Do not discard tins or pour paint into water courses, use
the facilities provided. It is best to allow paints to harden before disposal. Remainders of this product cannot be disposed of through the
municipal waste route or dumped without permit.

General

• The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk. Nautix can accept no responsibility for the performance of the product or for any loss or damage. The information contained in this sheet is liable to modification from time to time.

